



Solid Polymer Electrochemical Gas Sensing Technology

ES4-CO-10-01 Carbon Monoxide Gas Sensor
Datasheet

Easy Gas Sensor

ES4-CO-10 Carbon Monoxide Gas



» Part Number

01-ES4-CO-10-01

» Features

- 👉 Detects with high selectivity a wide variety of gases
- 👉 Long Lifetime > 5 years
- 👉 No-Poisoning
- 👉 Typical warm-up time in seconds
- 👉 Fast Response Time
- 👉 nA power consumption
- 👉 Linear Output
- 👉 No Zero Line Drift
- 👉 Better Signal to Noise Ratio
- 👉 Wide Temperature Range of -40°C to +55°C
- 👉 Excellent Sensitivity at low Temperatures
- 👉 No Leakage
- 👉 Small Size
- 👉 RoHS compliant

» Typical Applications

- 👉 Industrial Safety
- 👉 Leakage Detection
- 👉 Gas Manufacturing Process Monitoring
- 👉 Outdoor Air Quality
- 👉 Emission Monitoring
- 👉 Indoor Air Quality
- 👉 Medical & Health Care



» Technical Specifications

Performance

Sensitivity	35 nA/ppm \pm 15 nA/ppm
Zero Current	\pm 100nA
Range	0-10ppm
Maximum Overload	100ppm
Resolution (16Bit ADC)	0.01ppm
Response Time	$T_{50} < 10s$, $T_{90} < 30s$
Repeatability	< 1%
Linearity	Linear

Environment

Operating Temperature Range	-40 to +55°C
Operating Humidity Range	15-95 %RH. Non-condensing
Operating Pressure Range	800 to 1200 hPa
Storage Temperature	0 to 20°C (Optimum temp. 4 to 6°C)

Operation

Operating Principle	Amperometric, 3-electrode
Bias Voltage	0 mV
Recommended Load Resistor	100 Ω
Warm-Up Time	< 60 s

Lifetime


Long-Term Drift	< 1 %/month
Expected Lifetime	> 5 years
Zero Drift in Clean Air	< 0.2 ppm
Storage Life	12 months
Warranty	12 months

***Note:** Long-Term Drift may vary depending on storage conditions and usage.

Housing

Housing Material	PPO
Weight	< 6g

» Dimensions (Unit: mm)




» Cross Sensitivity

Gas	Formula	Test Concentration	Sensor Reading
Acetylene	C_2H_2	1 ppm	0 ppm
Ethanol	C_2H_6O	1 ppm	0 ppm
Ammonia	NH_3	1 ppm	0 ppm
Benzene	C_6H_6	1 ppm	0 ppm
Methane	CH_4	1 %	0 ppm
Carbon Dioxide	CO_2	10 %	0 ppm
Carbon Monoxide	CO	1 ppm	1 ppm
Chlorine	Cl_2	1 ppm	0 ppm
Ethylene	C_2H_4	1 ppm	0 ppm
Hydrogen	H_2	2000 ppm	150 ppm
Hydrogen Cyanide	HCN	1 ppm	0 ppm
Hydrogen Sulfide	H_2S	1 ppm	0 ppm
Nitric Oxide	NO	5 ppm	0 ppm
Nitrogen Dioxide	NO_2	1 ppm	0 ppm
Sulphur Dioxide	SO_2	1 ppm	0 ppm
Isopropanol	C_3H_8O	1 ppm	0 ppm

Note:

- 1) The above interference factors may vary due to different sensors and service life, please refer to the actual test results.
- 2) This table is not complete for all cross gases. Please contact us for other gases.
- 3) The above parameters are the test results at a temperature of 25°C, a relative humidity of 50%RH and a normal pressure environment. The performance of the sensor varies under different environmental conditions. If you have any questions, please contact us.
- 4) The above cross interferences are represented by a low concentration of the gas.

» Temperature Curve



Disclaimer

The EC Sense performance data stated above is based on data obtained under test conditions using the EC Sense gas distribution system and AQS test software. In the interest of continuous product improvement, EC Sense reserves the right to change design features and specifications without notice. We are not responsible for any loss, injury or damage caused by this. EC Sense assumes no responsibility for any indirect loss, injury or damage resulting from the use of this document, the information contained therein or any omissions or errors herein. This document does not constitute an offer to sell. The data it contains are for informational purposes only and cannot be considered a guarantee. Any use of the given data must be evaluated and determined by the user to comply with federal, state and local laws and regulations. All specifications outlined are subject to change without notice.

⚠️ Warning

EC Sense sensors are designed for use in a variety of environmental conditions. However, due to the principles and characteristics of solid polymer electrochemical sensors and to ensure normal use, users must strictly follow this article during storage, assembly and operation of the module. Avoid cleaning the sensors with alcohol, acetone or other strong solvents. General-purpose PCB circuit board application methods and illegal applications / violation of the application will not be covered by the warranty. Although our products are highly reliable, we recommend checking the module's response to the target gas prior to utilization to ensure on-site use. At the end of the product's service life, please do not discard any electronics in the domestic waste, instead follow the local governments electronic waste recycling regulations for disposal.



**Business Centre
Europe and the rest of the world**

EC Sense GmbH
Wangener Weg 3
82069 Hohenstaufen, Germany
Tel: +49(0)8178-99992-10 Fax: +49(0)8178-99992-11
Email: office@ecsense.com
www.ecsense.com, www.ecnose.de

**Business Centre
Asia**

Ningbo AQSystems Technology Co., Ltd.
F4-17 Building, Zhong Wu Technology Park No.228,
Jin Gu Bei Road, Yinzhou District NingBo,
Zhejiang Province, P.R. China Post Code: 315100
Tel: +86(0)574 88097236, 88096372
Email: info@aqsystems.cn
www.ecsense.cn, www.ecnose.de