



# Solid Polymer Electrochemical Gas Sensing Technology

**ES1-H<sub>2</sub>-5%-01 Hydrogen Gas Sensor  
Datasheet**

## Easy Gas Sensor

# ES1-H<sub>2</sub>-5% Hydrogen Gas



## » Part Number

01-ES1-H<sub>2</sub>-5%-01

## » Features

- 👉 Fast warm-up time
- 👉 Lower detection limit of 10 ppm
- 👉 High overload range of 20% vol.
- 👉 Broad operational temperature range from -40 °C to +55 °C
- 👉 Long lifetime (> 5 years)
- 👉 No humidity dependency
- 👉 No leakage

## » Typical Applications

- 👉 Hydrogen Leakage
- 👉 Environmental Monitoring
- 👉 Hydrogen Industrial Plants
- 👉 Energy Engineering
- 👉 Process Monitoring



## » Technical Specifications

### Performance

Sensitivity	0.2 nA/ppm ± 0.1 nA/ppm
Zero Current	± 3 nA
Range	0 - 5% vol.
Maximum Overload	> 20% vol. (expected)
Resolution (16Bit ADC)	0.001% vol.
Response Time	T <sub>50</sub> < 35 s, T <sub>90</sub> < 90 s
Repeatability	1.5 % (typically)
Linearity	Linear

**\*Note:** 1. Measured value for zero current depends on potentiostat electronics.  
2. Minimum recommended resolution for a 16Bit ADC.

### Environment

Operating Temperature Range	-40 °C to +55 °C
Operating Humidity Range	15 - 95% RH. Non-condensing
Operating Pressure Range	800 to 1200 hPa
Storage Temperature	0 °C to 20 °C (Optimum temp. 4 °C to 6 °C)

### Operation

Operating Principle	Amperometric, 3-electrode
Bias Voltage	0 mV
Recommended Load Resistor	100 Ω
Warm-Up Time	< 60 s

### Lifetime


Long-Term Drift	< 5 %/year
Expected Lifetime	> 5 years
Zero Drift in Clean Air	< 0.001% vol.
Storage Life	12 months
Warranty	12 months

**\*Note:** Long-Term Drift may vary depending on storage conditions and usage.

### Housing

Housing Material	PPO
Weight	< 0.7 g

## » Dimensions ( Unit: mm )



## » Cross Sensitivity

The "Test Concentration" was used to test the sensor. The "Sensor Reading" applies to the amount of the "Calculated Test Concentration".


Gas	Formula	Test Concentration	Calculated Test Concentration	Sensor Reading
Ethanol	C <sub>2</sub> H <sub>6</sub> O	20 ppm	1 ppm	0 ppm
Hydrogen	H <sub>2</sub>	-	4% vol.	4% vol.
Ammonia	NH <sub>3</sub>	100 ppm	1 ppm	0 ppm
Benzene *	C <sub>6</sub> H <sub>6</sub>	-	1 ppm	0 ppm
Methane	CH <sub>4</sub>	300 ppm	1% vol.	0 ppm
Carbon Dioxide *	CO <sub>2</sub>	-	10% vol.	0 ppm
Carbon Monoxide	CO	100 ppm	100 ppm	100 ppm
Ethylene	C <sub>2</sub> H <sub>4</sub>	200 ppm	1 ppm	0 ppm
Ethylene Oxide *	C <sub>2</sub> H <sub>4</sub> O	-	1 ppm	0 ppm
Isobutene *	C <sub>4</sub> H <sub>8</sub>	-	1 ppm	0 ppm
Methyl Mercaptan	CH <sub>4</sub> S	10 ppm	1 ppm	0 ppm

\* Reaction is not expected.

### Note:

- 1) The above interference factors may vary due to different sensors and service life, please refer to the actual test results.
- 2) This table is not complete for all cross gases. Please contact us for other gases.
- 3) The above parameters are the test results at a temperature of 25 °C, a relative humidity of 50% RH and a normal pressure environment. The performance of the sensor varies under different environmental conditions. If you have any questions, please contact us.
- 4) The above cross interferences are represented by a low concentration of the gas.

## » Temperature Curve



### Disclaimer

The EC Sense performance data stated above is based on data obtained under test conditions using the EC Sense gas distribution system and AQS test software. In the interest of continuous product improvement, EC Sense reserves the right to change design features and specifications without notice. We are not responsible for any loss, injury or damage caused by this. EC Sense assumes no responsibility for any indirect loss, injury or damage resulting from the use of this document, the information contained therein or any omissions or errors herein. This document does not constitute an offer to sell. The data it contains are for informational purposes only and cannot be considered a guarantee. Any use of the given data must be evaluated and determined by the user to comply with federal, state and local laws and regulations. All specifications outlined are subject to change without notice.

### ⚠ Warning

EC Sense sensors are designed for use in a variety of environmental conditions. However, due to the principles and characteristics of solid polymer electrochemical sensors and to ensure normal use, users must strictly follow this article during storage, assembly and operation of the module. Avoid cleaning the sensors with alcohol, acetone or other strong solvents. General-purpose PCB circuit board application methods and illegal applications or violation of the application will not be covered by the warranty. Although our products are highly reliable, we recommend checking the module's response to the target gas prior to utilization to ensure on-site use. At the end of the product's service life, please do not discard any electronics in the domestic waste, instead follow the local governments electronic waste recycling regulations for disposal.



**Business Centre  
Europe and the rest of the world**

EC Sense GmbH  
Wangener Weg 3  
82069 Hohenstaufen, Germany  
Tel: +49(0)8178-99992-10 Fax: +49(0)8178-99992-11  
Email: [office@ecsense.com](mailto:office@ecsense.com)  
[www.ecsense.com](http://www.ecsense.com)

**Business Centre  
Asia**

Ningbo AQSystems Technology Co., Ltd.  
6 Building, Zhong Wu Technology Park No.228,  
Jin Gu Bei Road, Yinzhou District NingBo,  
Zhejiang Province, P.R. China Post Code: 315100  
Tel: +86(0)574 88097236, 88096372  
Email: [info@aqsystems.cn](mailto:info@aqsystems.cn)  
[www.ecsense.com](http://www.ecsense.com)